



## PRESS RELEASE 2008

### GA 6622 and GA 7922 Gyorakes with side delivery

The new trailed GA 6622 / GA 7922 gyrorakes benefit from KUHN's very long experience in large capacity side delivery gyrorakes. They are aimed at farms requiring a high capacity, versatile and manoeuvrable tools.

They have a working width adjustable from 3.00 m to 5.80 m (GA 6622) or from 4,20 m to 7,30m (GA 7922) in « 1 windrow » position and up to 6.50 m (GA 6622) or 7,80m (GA 7922) in « 2 windrow » position. The latter position is of particular interest when making night windrows or for turning over windrows.

Being pulled, these Gyorakes provide exceptional manoeuvrability and are adapted to low horse powered tractors.

The new GA 6622 and GA 7922 Gyorakes, which will replace the GA 6522 and GA 7822, present other significant and interesting developments for the user, with in particular:

- Removable tine arms and foldable guards to reduce the transport and parking width to the minimum,
- The new rear rotor pendulum type 3D articulation, with a lower centre of gravity,
- A new windrow curtain with hydraulic adjustment and folding.

The other main assets of the GA 6622 and GA 7922, retained from previous generations, are:

- Drawbar hitch mounted on a parallelogram: the front part of the drawbar is always in horizontal position.
- For a longer service life even in green and dense forage, the 11 or 12 arm rotors are driven by MASTERDRIVE® gearboxes. This patented two stage reduction gearbox of new design enables reducing considerably stress on the mechanical parts..
- Windrowing to the right for a greater driving comfort.
- Passing over even very voluminous windrows as well as headland turns are facilitated thanks to the high rotor clearance (55 cm).
- Very large undercarriages and up to 6 « Hyper-balloon » wheels per rotor (bogie axle on each rotor and 2 complementary wheels on the rear rotor) ensure perfect stability in all circumstances.
- An articulated chassis and a rear rotor with 3D suspension (transversal and longitudinal ground following) ensures perfect adaptation to ground contours and consequently crop harvested is not soiled by impurities.
- Hydraulic setting and folding of the windrow curtain as from the tractor cab for higher driving comfort,
- Authorization for travelling at 40 km/h in most countries.